



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
ITF-TCC	Static electric tunnel oven with stainless steel mesh belt 830 mm wide, cooking chamber 870x1500x110h mm, V.400/3, Kw 34.00, Weight 233 Kg, external dimensions 1420x2470x410h mm	

PROFESSIONAL DESCRIPTION

STATIC ELECTRIC TUNNEL PIZZA OVEN, MODULAR, STACKABLE :

- made of stainless steel ;
- **83 cm wide copper-coated steel mesh conveyor belt** ;
- **hob and top with stainless steel armored heating elements** ;
- **internal dimensions of the cooking chamber mm L 870 x D 1500 x H 110** ;
- **static cooking system** ;
- **adjustable belt speed** ;
- thanks to the **exceptional insulation** the **external temperature of the oven remains at 30°C** to always guarantee maximum safety during working hours;
- **thermal insulation** guaranteed by the choice of the best materials on the market;
- **+30% cooking capacity compared to conventional ovens** ;
- **digital control of separate hob and ceiling temperatures** ;
- **450° C maximum cooking temperature** ;
- **digital control of separate hob and ceiling temperatures** ;
- **2 removable crumb trays** positioned at the entrance and exit of the tunnel simplify oven cleaning;
- **adjustable inlet and outlet shutters** ;
- **simplicity of use, perfect cooking with very low consumption** allow it to be used even by non-specialised personnel;
- **Tunnel is excellent for cooking multiple products** , such as pizzas, focaccias, Arabic bread, tortillas, piadinas, bruschetta, crostini, chicken wings, meats;
- **special configurations** on request.

Surrender :

- pizza diam. 15 cm - 765 pcs/hour;
- pizza diam. 20 cm - 510 pcs/hour;
- pizza diam. 25 cm - 306 pcs/hour;
- pizza diam. 30 cm - 238 pcs/hour;
- pizza diam. 35 cm - 136 pcs/hour;
- pizza diam. 45 cm - 81 pcs/hour;
- pizza diam. 50 cm - 65 pcs/hour.

Accessories/Options :

- base support can be requested with a height of 760/560/360 mm
- it is possible to have the oven with the belt in **REFRACTORY STRAP**
- Encoder kit that allows you to digitally manage times and temperatures of the top and bottom, the PCL allows you to set up to 25 programs extremely quickly and precisely, keeping the cooking values constant thanks to an encoder applied to the motor.


CE mark

Made in Italy

TECHNICAL CARD

power supply	Trifase
Volts	V 400/3
frequency (Hz)	50
motor power capacity (Kw)	34,00
net weight (Kg)	233
breadth (mm)	1420
depth (mm)	2470
height (mm)	410

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
ITF-STCC1 	Base support for tunnel oven Mod.TCC Base support for tunnel oven Mod.TCC, complete with wheels, Weight 48 Kg, dim.mm.1330x1510x760h	

ITF-KITENCODER



TECHNOCHEF - Encoder kit for pizza tunnel ovens, Mod.KITENCODER

Encoder Kit allows you to digitally manage times and temperatures of the top and bottom, with the possibility of setting up to 25 programs.




KIT ENCODER OPTIONAL

Consente di gestire in modo digitale tempi di cottura e temperature di cielo e piano cottura.






VISTA DALL'ALTO
TOP VIEW




Tunnel	A	B
TCA	177	108
TCB	211	121
TCX	247	142


1 CAMERA + SUPPORTO ALTO
1 DECK + HIGH STAND



2 CAMERE + SUPPORTO MEDIO
2 DECKS + MEDIUM STAND



3 CAMERE + SUPPORTO BASSO
3 DECKS + LOW STAND



DATI TECNICI
TECHNICAL CHART



Tunnel	Dimensioni interne (cm)			Dimensioni esterne (cm)			Tappeto	Peso	Alimentazione	Potenza	Potenza	Assorbimento	Temperatura
	Internal dimensions (cm)			External dimensions (cm)			Conveyor	Weight	Supply	Power	Power	Absorption	Temperature
	A/H	L/W	P/D	A/H	L/W	P/D	L/W	KG	V/Ph/Hz	KW	KW/h	Ampere	°C
TCA - DECK	11	53	80	41	108	177	45	114	400/3/50-60	12,5	6	19	0/450
TCB - DECK	11	67	114	41	122	211	63	163	400/3/50-60	19,5	10	30	0/450
TCX - DECK	11	87	150	41	142	247	83	233	400/3/50-60	34	17	52	0/450
STCA1 - STAND				76/56/36	99	81		40					
STCB1 - STAND				76/56/36	113	115		43					
STCC1 - STAND				76/56/36	133	151		48					