



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-PZ2600TN-FC</b>	REFRIGERATED PIZZA COUNTER with 2 DOORS, GRANITE top, temperature -2 ° / + 8 ° C, Ventilated, ECOLOGICAL Gas R600a in Class C, V 230/1, Kw 0,235, Weight 233 Kg, dim.mm.1510x800x1000h.	<b>€ 985,54</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 25 to 35 days

**PROFESSIONAL DESCRIPTION**

**2 DOOR PIZZA COUNTER, with GRANITE WORKTOP and UPSTAND, operating temperature -2 ° / + 8 ° C, CLASS C, FORCOLD brand :**

- **structure** in **AISI 201 stainless steel** ;
- 3-sided granite worktop;
- **2 refrigerated compartments** able to accommodate **600x400x70h mm bread boxes**
- operating temperature -2 ° / + 8 ° C;
- **capacity** **lt . 390;**
- **ventilated refrigeration** ;
- **ECOLOGICAL gas R600a** ;
- **Energy CLASS C** ;
- **incorporated unit removable** for easy maintenance;
- front panel that can be opened with a key;
- **circular flow of cold air** so as not to directly touch the product;
- **electronic temperature control with digital thermostat** ;
- electrical resistance around the door frame to eliminate condensation;
- **automatic defrost** with electric resistance and automatic control of the defrost temperature;
- **automatic evaporation of condensation water** ;
- anti-corrosion treated evaporator;
- insulation thickness: 60 mm;
- Max temp. Operating / Ambient humidity ° c / rh + 35/50%
- door with return spring;
- door gasket removable without tools;
- bottom with rounded corners;
- **height-adjustable stainless steel feet** ;
- possibility to lean against the wall.

**Included :**



- 7 pairs of door rails (no grille supplied)

**CE mark**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,235
<b>net weight (Kg)</b>	233
<b>breadth (mm)</b>	1510
<b>depth (mm)</b>	800
<b>height (mm)</b>	1000

**TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<p><b>FO-GRP64</b></p> 	<p><b>Forcar - Plasticized Grid</b> 600x400 mm plastic coated grid</p>	<p><b>€ 11,24</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days</p>
<p><b>FO-GUT</b></p> 	<p><b>Forcar - Driving Couple</b> Pair of trays for trays</p>	<p><b>€ 17,18</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days</p>

FO-GAR



**Forcar - Pair of anti-tilt guides**  
Pair of anti-tilt guides for grill

**€ 20,04**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 4 to 9 days

