



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
FC-G-GN650TN-FC	1 Door Refrigerator Cabinet, Professional, It.650, Temp.-2°/+8°C, ECOLOGICAL in Class D, Gas R290, Ventilated, Gastronorm 2/1, V.230/1, Kw.0,305, Weight 120 Kg , dim.mm.740x830x2010h.	€ 784,58 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days
PROFESSIONAL DESCRIPTION		

1-door FRIDGE CABINET, capacity 650 litres, operating temperature -2°/+8°C, ECOLOGICAL in Class D:

- made of **AISI 201 stainless steel** ;
- **chamber bottom with rounded corners** ;
- external bottom panels in galvanized sheet metal;
- **door with return spring** and reversible;
- door **locking with key** ;
- door seal removable without tools;
- suitable for containing **Gastro-Norm 2/1 grills or containers (650x530 mm)** ;
- **ventilated refrigeration** ;
- operating temperature -2°/+8°C;
- **electronic temperature control** with digital thermostat;
- anti-corrosion treated evaporator;
- engine compartment with insulated sides;
- ECOLOGICAL GAS **R290** Refrigerating Group;
- **automatic defrost** ;
- **automatic evaporation of condensation water** ;
- maximum ambient temperature: +38°C;
maximum ambient humidity: 60% HR;
- insulation thickness 60 mm;
- **interior light** ;
- Height-adjustable stainless steel feet.

Supplied :

- n.3 Gastro-Norm 2/1 grills
- n.6 guides


CE mark

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,305
net weight (Kg)	120
gross weight (Kg)	127
breadth (mm)	740
depth (mm)	830
height (mm)	2010





 **ENERG** Y IJA
енергия - ενεργεια IE IA


FORCOLD G-GN650TN-FC


A
B
C
D
E
F
G


D

ENERGIA · ЕНЕРГИЯ · ENERGIA
ENERGIA · ENERGY · ENERGIE
ENERGI

933
kWh/annum

 1L
440 L

 -L

 **4**
30°C ~ 55%

2015/1094-1

TECHNOCHEF.IT