



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
FC-M-GN4100BT-FC	Freezer Freezer Table 4 Doors, with Monobloc, plug-in system, capacity 553 litres, operating temperature -18°/-22°C, Gastronorm 1/1, ventilated, ECOLOGICAL in Class E, Gas R290, V.230 /l, Kw.0,675, Weight 144 Kg, dim.mm.2230x700x850h	€ 1.304,88 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days
PROFESSIONAL DESCRIPTION		

FREEZING TABLE - 4 DOOR FREEZER, with MONOBLOC, PLUG-IN SYSTEM, capacity 553 litres, temperature -18°C /-22°C, Gastronorm 1/1 (mm 530x325)

- **AISI 201 stainless steel structure,**
- **ventilated refrigeration ;**
- **compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);**
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- **monobloc in highly thermally insulating and completely recyclable plastic material ;**
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- **circular flow of the cold air so as not to directly touch the product ;**
- **electronic temperature control with digital thermostat ;**
- operating temperature -18°/-22°C;
- **electric resistance around the door frame to eliminate condensation ;**
- **automatic defrost with electric resistance and automatic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- **height-adjustable stainless steel feet ;**
- possibility of leaning against the wall;
- **ECOLOGICAL refrigeration unit with R290 gas ;**
- **insulation thickness 60 mm ;**
- max ambient temperature/humidity: +35 °C / 55%HR;
- internal dimensions (mm): 1772 x 630 x 560h;
- external dimensions (mm): 2230 x 700 x 850h.

Supplied :

- n.4 GN 1/1 grids (325x530 mm)
- n.6 guides.

Options/Accessories :


- pair of guides for GN 1/1 grill
- GN 1/1 plasticized grill
- kit of 4 wheels with a diameter of 120 mm, two of which with brakes

CE mark
Made in ASIA

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,675
net weight (Kg)	144
gross weight (Kg)	171
breadth (mm)	2230
depth (mm)	700
height (mm)	850

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<p>FOGRP11</p> 	<p>GN 1/1 plasticized grid Gastronorm 1/1 plasticized grid</p>	<p>€ 8,67 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days</p>

FOCG11



Pair of guides for GN 1/1 grid support
Pair of guides for GN 1/1 grid support

€ 11,56

VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days

FO-RUO120



Forcar - 4 wheels kit, 2 with brake
4 wheels kit with 120 mm diameter, 2 of which with brake.

€ 78,62

VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days