



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-M-GN2200BT-FC</b>	Freezer Freezer Table, 2 Doors and Backsplash, with Monoblock, Plug-in System, capacity 282 litres, temp. -18°/-22°C, Gastronorm 1/1, Ventilated, ECOLOGICAL in Class E, Gas R290, V.230/1, Kw.0,675, Weight 96 Kg, dim.mm.1360x700x950h	<p><b>€ 1.010,32</b>  <i>VAT excluded</i>  <b>Shipping to be calculated</b>  <b>Delivery</b> from 8 to 15 days</p>
<b>PROFESSIONAL DESCRIPTION</b>		

**FREEZING TABLE - FREEZER 2 DOORS and BACKPACK, with MONOBLOC, PLUG-IN SYSTEM, capacity 282 litres, temperature -18°C /-22°C, Gastronorm 1/1, ECOLOGICAL in Class E:**

- **AISI 201 stainless steel structure;**
- **ventilated refrigeration ;**
- **compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);**
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- **monobloc in highly thermally insulating and completely recyclable plastic material ;**
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- **electronic temperature control with digital thermostat ;**
- operating temperature -18°/-22°C;
- electric resistance around the door frame to eliminate condensation;
- **automatic defrost with electric resistance and automatic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- **height-adjustable stainless steel feet ;**
- **ECOLOGICAL refrigeration unit with R290 gas ;**
- **insulation thickness 60 mm ;**
- max ambient temperature/humidity: +35 °C / 55%HR;
- internal dimensions (mm): 900 x 530 x 560h;
- external dimensions (mm): 1360 x 700 x 950h.

**Supplied :**

- n.2 GN 1/1 grids (325x530 mm)
- n.4 guides.

**Options/Accessories :**

- pair of guides for GN 1/1 grill
- GN 1/1 plasticized grill
- kit of 4 wheels with a diameter of 120 mm, two of which with brakes


**CE mark**

**Made in ASIA**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,675
<b>net weight (Kg)</b>	96
<b>gross weight (Kg)</b>	114
<b>breadth (mm)</b>	1360
<b>depth (mm)</b>	700
<b>height (mm)</b>	950

**TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
FOGRP11 	<b>GN 1/1 plasticized grid</b> Gastronorm 1/1 plasticized grid	<b>€ 8,67</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days

**FOCG11**



**Pair of guides for GN 1/1 grid support**  
Pair of guides for GN 1/1 grid support

**€ 11,56**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 4 to 9 days

**FO-RUO120**



**Forcar - 4 wheels kit, 2 with brake**  
4 wheels kit with 120 mm diameter, 2 of which with brake.

**€ 78,62**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 4 to 9 days