



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>MZ691.AG</b>	HOT MAINTENANCE trolley, 2 doors with VENTILATED HEATING for 36 Gastro-Norm 1/1 PANS with 77 mm pitch between guides, V. 230/1, Kw 3.0 - dimensions 1220x790x1995h mm	<b>€ 2.336,32</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery from 8 to 15 days</b>

**PROFESSIONAL DESCRIPTION**

**HOT MAINTENANCE trolley for 36 Gastro-Norm 1/1 PANS, pitch between guides 77 mm :**

- made entirely of **AISI 304-18/10 stainless steel sheet, Scotch-Brite finish** ;
- **double wall structure** , made with **sandwich panels insulated** with expanded polyurethane and aluminum positioned between the two sheet metal walls;
- **Front swing door that opens 270° with rubber seal and snap opening handle;**
- **pair of push handles positioned on both short sides** , with **PVC handle supports**, **AISI 304-18/10 stainless steel** grip tube, the **handles can be used even with the doors open;**
- illuminated power switch with **mains presence indicator light** ;
- **temperature controlled** by a **digital thermostat-thermometer** , a red light signals the functioning of the resistance;
- **removable VENTILATED HEATING system for easy and convenient cleaning;**
- internal supports with 'C' profiles with anti-tipping function, 77 mm pitch;
- **wheels with a diameter of 125 mm** , **two swivel** with brake and **two fixed** with galvanized steel support;
- **perimeter bumper in gray anti-track rubber.**
- **OPTIONAL - ACCESSORIES:**
- **Door lock;**
- **Manual humidifier.**

**MADE IN ITALY**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	3
<b>breadth (mm)</b>	1320

<b>depth (mm)</b>	750
<b>height (mm)</b>	2000