







TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973

CODE	DESCRIPTION	PRICE/DELIVERY
SL-KV	Suction cups kit (N.4)	
PROFESSIONAL DESCRIPTION		
TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
SL-CPS350V 	Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 360 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 155 kg, dim.mm.620x620x1860h	
SL-CPS250V 	Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 230 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 125 kg, dim.mm.450x620x1860h	
SL-CPS450V 	Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 427 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 170 kg, dim.mm.720x620x1860h	
SL-CPS350R 	Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 6 rotating shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 6 rotating glass shelves, capacity 360 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 155 kg, dim.mm.620x620x1860h	

SL-CPS450R**Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 6 rotating shelves, CURVE Line**

Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 6 rotating glass shelves, capacity 427 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 170 kg, dim.mm.720x620x1860h

SL-CGL250S**TECHNOCHEF - Vetrina Freezer for Gelateria 1 Door, Temp.-15°-25°C, It.250, Mod.CGL250S**

Freezer-Freezer display case for ice cream parlor 1 door, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 6 rectangular shelves measuring 295x460 mm, capacity 250 lt, V.230/1, Kw.0 ,58, Weight 134 Kg, dim.mm.450x620x1860h

SL-CGL350S**TECHNOCHEF - Vetrina Freezer for Gelateria, Temp.-15°- 25°C, 1 Door, It.360, Mod.CGL350S**

Freezer-Freezer display case for ice cream parlor 1 door, Curve Line, capacity 360 liters, temperature -15°/-25°C, static refrigeration, with 4 display sides, 6 square shelves measuring 460x460 mm, V.230/1, Kw.0 ,7, Weight 146 Kg, dim.mm.620x620x1860h

SL-CPS600V**Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line**

Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 541 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 176 kg, dim.mm.900x620x1860h

SL-CGL450S**TECHNOCHEF - Vetrina Freezer for Gelateria, Temp.-15°-25°C, 1 Door, It.427, Mod.CGL450S**

Freezer-Freezer display case for ice cream parlor 1 door, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 6 rectangular shelves measuring 560x440 mm, capacity 427 lt, V.230/1, Kw.0 ,7, Weight 165 Kg, dim.mm.720x620x1860h

SL-CGL600S**TECHNOCHEF - Vetrina Freezer for Gelateria 1 Door, Temp.-15°-25°C, It.541, Mod.CGL600S**

Freezer-Freezer display case for ice cream parlor 1 door, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 6 rectangular shelves measuring 734x460 mm, capacity 541 litres, V.230/1, Kw. 0.7, weight 192 kg, dim.mm.900x620x1860h

SL-CGL450G2T**TECHNOCHEF - Refrigerated Pastry Display Case, Temp.+5°-20°C, 1 Door, 427 lt, Mod.CGL450G2T**

Multi-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve Line, with 4 display sides, 5 rectangular shelves measuring 565x445 mm, capacity 427 liters, V.230/1, Kw.0.75, Weight 186 Kg, dim.mm.720x620x1860h

SL-CPS800V**Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 4 rectangular shelves, CURVE Line**

Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 4 rectangular glass shelves, capacity 832 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 260 kg, dim.mm.900x900x1860h

SL-CGL450R2T**TECHNOCHEF - Refrigerated Pastry Display Case,****Temp.+5°-20°C, 1 Door, 427 lt., Mod.CGL450R2T**

Multi-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve Line, with 4 display sides, 5 rotating glass shelves Ø 452, capacity 427 liters, V.230/1, Kw.0.54 , Weight 186 Kg, dim.mm.720x620x1860h

SL-CGL600G2T**TECHNOCHEF - Refrigerated Pastry Display Case,****Temp.+5°-20°C, 1 Door, 541 lt, Mod.CGL600G2T**

Multi-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve Line, with 4 display sides, 5 rectangular shelves measuring 747x445 mm, capacity 541 liters, V.230/1, Kw.0.85, Weight 205 Kg, dim.mm.900x620x1860h

SL-CPG520V/S**TECHNOCHEF - Combined display case for ice cream and pastry, temp. -15°-25°C/+4°+10°C, Mod.CPG520V/S**

Combined display case for ice cream/pastry shop 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, 4 display sides, 3 grilled shelves + 3 glass shelves, ventilated/static refrigeration, capacity liters .230+260, V.230/1, Kw.0.37+0.42, dim.mm.810x620x1925h

SL-CPS700V/V**Refrigerated pastry display case with 2 doors, 4 display sides, 10 rectangular shelves, CURVE line**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 10 rectangular glass shelves, capacity 742 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54+0.54, weight 294 kg, dim.mm.1180x620x1860h

SL-CPS700V/R**Refrigerated Pastry Display Case 2 Doors, 4 display sides, 5 rectangular shelves + 6 rotating shelves**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 5 rectangular shelves + 6 rotating shelves, capacity 742 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0 ,54+0.54, Weight 294 Kg, dim.mm.1180x620x1860h

SL-CPG900S/V**TECHNOCHEF - Combined display case for ice cream and pastry, temp. -15°-25°C/+4°+10°C, Mod.CPG900S/V**

Combined display case for ice cream/pastry shop 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, with 4 display sides, 6 static shelves + 5 rectangular glass shelves, ventilated/static refrigeration, 848 lt, V.230/1, Kw.0.70+0.54, dim.mm.1380x620x1860h

SL-CPS700R/R**Refrigerated Pastry Display Case 2 Doors, 4 display sides, 12 rotating shelves, CURVE Line**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 12 rotating glass shelves, capacity 742 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54 +0.54, weight 294 kg, dim.mm.1180x620x1860h

SL-CPS900V/V**Refrigerated Pastry Display Case 2 Doors, 4 display sides, 10 rectangular shelves, Curve Line**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 10 rectangular glass shelves, capacity 848 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54+0.54, weight 301 kg, dim.mm.1380x620x1860h

SL-CPG900S/R**TECHNOCHEF - Combined display case for ice cream and pastry, temp. -15°-25°C/+4°+10°C, Mod.CPG900S/R**

Combined display case for ice cream/pastry shop, 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, 4 display sides, 6 rectangular shelves + 6 rotating shelves, ventilated/static refrigeration, capacity liters. 848, V.230/1, Kw.0.70+0.54, dim.mm.1380x620x1860h

SL-CPS900V/R**Refrigerated Pastry Display Case 2 Doors, 4 display sides, 5 rectangular shelves + 6 rotating shelves**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 5 rectangular shelves + 6 rotating shelves, capacity 848 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54+0.54, Weight 301 Kg, dim.mm.1380x620x1860h

SL-CPS900R/R**Refrigerated Pastry Display Cabinet 2 Doors, 4 display sides, 12 rotating shelves, Curve Line**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 12 rotating glass shelves, capacity 848 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54+0.54, weight 301 kg, dim.mm.1380x620x1860h

SL-CPS1200V/V**Refrigerated Pastry Display Case 2 Doors, 4 display sides, 10 rectangular shelves, Curve Line**

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 10 rectangular glass shelves, capacity 1,082 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54 +0.54, weight 318 kg, dim.mm.1750x620x1860h

SL-CGL700S/S**TECHNOCHEF - Vetrina Freezer for Gelateria 2 Sizes, Temp.-15°-25°C, It.742, Mod.CGL700S/S**

Freezer-Freezer display case for ice cream parlor with 2 doors, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 12 square shelves measuring 460x460 mm, capacity 742 litres, V.230/1, Kw. 0.7+0.7, weight 270 kg, dim.mm.1180x620x1860h

SL-CPG900G2T/V**TECHNOCHEF - Combined display case for ice cream and pastry, temp.-15°-25°C/+4°+10°C, Mod.CPG900G2T/V**

Combined display case for ice cream/pastry shop 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, with 4 display sides, 5 grilled shelves + 5 glass shelves, ventilated/static refrigeration, capacity lt.848, V.230/1, Kw.0.70+0.54, dim.mm.1380x620x1860h

SL-CGL900S/S**Vetrina Congelante per Pasticceria-Gelateria 2 Porte, 2 Vani, 2 Motori, Temp.-15°-25°C // -15°-25°C.**

Freezer-Freezer display case for ice cream shop, capacity 848 litres, 2 doors, 2 temperatures. -15°/-25°C // -15°-25°C. , 2 separate compartments, 2 MOTORS, static, with 4 display sides, 12 shelves measuring 560x460 mm, V.230/1, Kw.0.7+0.7, Weight 287 Kg, dim.mm.1380x620x1860h

SL-CGL900G2T/G2T**Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, 848 lt, Mod.CGL900G2T/G2T**

Multi-temperature display case from +5° to -20°C for 2-door pastry shops, ventilated refrigeration, Curve Line, with 4 display sides, 10 rectangular shelves measuring 565x445 mm, capacity 848 liters, V.230/1, Kw.0.75+0.75, weight 329 kg, dim.mm.1380x620x1860h

SL-CGL900G2T/R2T

Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, 848 lt, Mod.CGL900G2T/RG2T
Multi-temperature display case from +5° to -20°C for 2-door pastry shops, ventilated refrigeration, Curve Line, with 4 display sides, 5 gridded shelves + 5 rotating shelves, capacity 848 liters, V.230/1, Kw.0.75 +0.75, weight 329 kg, dim.mm.1380x620x1860h

SL-CGL1200S/S

TECHNOCHEF - Vetrina Freezer for Gelateria 2 Sizes, Temp.-15°-25°C, lt.1082, Mod.CGL1200S/S
Freezer-Freezer display case for ice cream shop with 2 doors, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 12 rectangular shelves measuring 734x460 mm, capacity 1082 litres, V.230/1, Kw. 0.7+0.7, weight 348 kg, dim.mm.1750x620x1860h

SL-CGL900R2T/R2T

Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, 848 lt, Mod.CGL900R2T/R2T
Multi-temperature display case from +5° to -20°C for pastry shops, 2 doors, ventilated refrigeration, Curve Line, with 4 display sides, 10 rotating glass shelves, capacity 848 liters, V.230/1, Kw.0.75+0.75, Weight 329 Kg, dim.mm.1380x620x1860h

SL-CPS1300V/V/V

Refrigerated Pastry Display Case 3 Doors, 4 display sides, 15 rectangular shelves, CURVE Line
Refrigerated pastry display case with 3 doors, CURVE line, with 4 display sides, 15 rectangular glass shelves, capacity 1388 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54 +0.54+0.54, weight 370 kg, dim.mm.2050x620x1860h

SL-CPS1300R/R/V

Refrigerated Pastry Display Case 3 Doors, 4 display sides, 10 rectangular shelves + 6 rotating shelves
Refrigerated pastry display case with 3 doors, CURVE line, 4 display sides, 10 rectangular shelves + 6 rotating shelves, capacity 1388 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54+0.54+0.54, weight 370 kg, dim.mm.2050x620x1860h

SL-CGL1300S/S/S

TECHNOCHEF - Vetrina Freezer for Gelateria 3 Sizes, Temp.-15°-25°C, lt.1388, Mod.CGL1300S/S/S
Freezer-Freezer display case for ice cream shop with 3 doors, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 18 rectangular shelves measuring 560x460 mm, capacity 1388 litres, V.230/1, Kw. 0.7+0.7+0.7, weight 424 kg, dim.mm.2050x620x1860h

SL-CPG1300S/S/V

TECHNOCHEF - Combined display case for ice cream/pastry shop, temp. -15°-25°C/+4°+10°C, Mod.CPG1300S/S/V
Combined display case for ice cream/pastry shop, 3 doors, temp. -15°-25°C/+4°+10°C, Curve Line, 4 display sides, 12 static shelves + 5 glass shelves, ventilated/static refrigeration, capacity liters .1388, V.230/1, Kw.0.7+0.7+0.54, dim.mm.2050x620x1860h

SL-CGL1200G2T/G2T

TECHNOCHEF - Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, lt.1082, Mod.CGL1200G2T/G2T
Multi-temperature display case from +5° to -20°C for 2-door pastry shops, ventilated refrigeration, Curve Line, with 4 display sides, 10 rectangular shelves measuring 747x445 mm, capacity 1082 liters, V.230/1, Kw.0.85+0.85, weight 382 kg, dim.mm.1750x620x1860h

SL-CPG1300S/S/R



TECHNOCHEF - Combined display case for ice cream/pastry shop, temp. -15°-25°C/+4°+10°C, Mod.CPG1300S/S/R

Combined display case for ice cream/pastry shop, 3 doors, temp. -15°-25°C/+4°+10°C, Curve Line, 4 display sides, 12 static shelves + 6 rotating shelves, ventilated/static refrigeration, capacity liters. 1388, V.230/1, Kw.0.7+0.7+0.54, dim.mm.2050x620x1860h

SL-CGL1300G/G/G2T



TECHNOCHEF - Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, lt.1388, Mod.CGL1300G/G/G2T

Multi-temperature display case from +5° to -20°C for 3-door pastry shops, ventilated refrigeration, Curve Line, with 4 display sides, 15 rectangular shelves measuring 565x445 mm, capacity 1388 litres, V.230/1, Kw.0.75+0.75+0.75, weight 478 kg, dim.mm.2050x620x1860h