

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973

| CODE | DESCRIPTION | PRICE/DELIVERY |
|--------------|-------------|----------------|
| GL 1/2021/00 | | |

SL-KP25/80 Adjustable feet kit

PROFESSIONAL DESCRIPTION

TECHNICAL CARD

CODE/PICTURES DESCRIPTION PRICE/DELIVERY

SL-CPS350V



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 360 litres, operating temperature +4°/+10°C, ventilated

360 litres, operating temperature +4°/+10°C, ventilate refrigeration, V.230/1, Kw. 0.54, weight 155 kg, dim.mm.620x620x1860h

SL-CPS250V



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 230 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 125 kg, dim.mm.450x620x1860h

SL-CPS450V



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 427 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 170 kg, dim.mm.720x620x1860h

SL-CPS350R



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 6 rotating shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE I

Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 6 rotating glass shelves, capacity 360 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 155 kg, dim.mm.620x620x1860h

SL-CPS450R



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 6 rotating shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 6 rotating glass shelves, capacity 427 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 170 kg, dim.mm.720x620x1860h

SL-CGL250S



TECHNOCHEF - Vetrina Freezer for Gelateria 1 Door, Temp.-15°-25°C, lt.250, Mod.CGL250S

Freezer-Freezer display case for ice cream parlor 1 door, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 6 rectangular shelves measuring 295x460 mm, capacity 250 lt, V.230/1, Kw.0 ,58, Weight 134 Kg, dim.mm.450x620x1860h

SL-CGL350S



TECHNOCHEF - Vetrina Freezer for Gelateria, Temp.-15°- 25°C, 1 Door, lt.360, Mod.CGL350S

Freezer-Freezer display case for ice cream parlor 1 door, Curve Line, capacity 360 liters, temperature -15°/-25°C, static refrigeration, with 4 display sides, 6 square shelves measuring 460x460 mm, V.230/1, Kw.0 ,7, Weight 146 K g, dim.mm.620x620x1860h

SL-CPS600V



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 5 rectangular shelves, CURVE Line

Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 5 rectangular glass shelves, capacity 541 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 176 kg, dim.mm.900x620x1860h

SL-CGL450S



TECHNOCHEF - Vetrina Freezer for Gelateria, Temp.-15°-25°C, 1 Door, lt.427, Mod.CGL450S

Freezer-Freezer display case for ice cream parlor 1 door, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 6 rectangular shelves measuring 560x440 mm, capacity 427 lt, V.230/1, Kw.0 ,7, Weight 165 Kg, dim.mm.720x620x1860h

SL-CGL600S



TECHNOCHEF - Vetrina Freezer for Gelateria 1 Door, Temp.-15°-25°C, lt.541, Mod.CGL600S

Freezer-Freezer display case for ice cream parlor 1 door, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 6 rectangular shelves measuring 734x460 mm, capacity 541 litres, V.230/1, Kw. 0.7, weight 192 kg, dim.mm.900x620x1860h

SL-CGL450G2T



TECHNOCHEF - Refrigerated Pastry Display Case, Temp.+5°-20°C, 1 Door, 427 lt, Mod.CGL450G2T

Multi-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve Line, with 4 display sides, 5 rectangular shelves measuring 565x445 mm, capacity 427 liters, V.230/1, Kw.0.75, Weight 186 Kg, dim.mm.720x620x1860h

SL-CPS800V



Refrigerated Pastry Display Cabinet 1 Door, 4 display sides, 4 rectangular shelves, CURVE Line Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 4 rectangular glass shelves, capacity 832 litres, operating temperature +4°/+10°C, ventilated

refrigeration, V.230/1, Kw. 0.54, weight 260 kg, dim.mm.900x900x1860h

SL-CGL450R2T



TECHNOCHEF - Refrigerated Pastry Display Case, Temp.+5°-20°C, 1 Door, 427 lt., Mod.CGL450R2T Multi-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve

mult-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve Line, with 4 display sides, 5 rotating glass shelves Ø 452, capacity 427 liters, V.230/1, Kw.0.54, Weight 186 Kg, dim.mm.720x620x1860h

SL-CGL600G2T



TECHNOCHEF - Refrigerated Pastry Display Case, Temp.+5°-20°C, 1 Door, 541 lt, Mod.CGL600G2T Multi-temperature display case from +5° to -20°C for

Multi-temperature display case from +5° to -20°C for pastry shops, 1 door, ventilated refrigeration, Curve Line, with 4 display sides, 5 rectangular shelves measuring 747x445 mm, capacity 541 liters, V.230/1, Kw.0.85, Weight 205 Kg, dim.mm.900x620x1860h

SL-CPG520V/S



TECHNOCHEF - Combined display case for ice cream and pastry, temp. -15°-25°C/+4°+10°C, Mod.CPG520V/S

Combined display case for ice cream/pastry shop 2 doors, temp. $\cdot 15^{\circ} \cdot 25^{\circ} \text{C}/+4^{\circ} + 10^{\circ} \text{C}$, Curve Line, 4 display sides, 3 grilled shelves + 3 glass shelves, ventilated/static refrigeration, capacity liters $\cdot 230 + 260$, $\cdot V.230/1$, Kw.0.37+0.42, dim.mm.810x620x1925h