





CODE	DESCRIPTION	PRICE/DELIVERY
SL-VSP70/90	Mirror glass (N.1)	
PROFESSIONAL DESCRIPTION		
TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
SL-CPS700V/V 	Refrigerated pastry display case with 2 doors, 4 display sides, 10 rectangular shelves, CURVE line Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 10 rectangular glass shelves, capacity 742 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54+0.54, weight 294 kg, dim.mm.1180x620x1860h	
SL-CPS700V/R 	Refrigerated Pastry Display Case 2 Doors, 4 display sides, 5 rectangular shelves + 6 rotating shelves Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 5 rectangular shelves + 6 rotating shelves, capacity 742 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0,54+0.54, Weight 294 Kg, dim.mm.1180x620x1860h	
SL-CPG900S/V 	TECHNOCHEF - Combined display case for ice cream and pastry, temp. -15°-25°C/+4°+10°C, Mod.CPG900S/V Combined display case for ice cream/pastry shop 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, with 4 display sides, 6 static shelves + 5 rectangular glass shelves, ventilated/static refrigeration, 848 lt, V.230/1, Kw.0.70+0.54, dim.mm.1380x620x1860h	
SL-CPS700R/R 	Refrigerated Pastry Display Case 2 Doors, 4 display sides, 12 rotating shelves, CURVE Line Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 12 rotating glass shelves, capacity 742 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54 +0.54, weight 294 kg, dim.mm.1180x620x1860h	

SL-CPS900V/V

Refrigerated Pastry Display Case 2 Doors, 4 display sides, 10 rectangular shelves, Curve Line
Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 10 rectangular glass shelves, capacity 848 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54+0.54, weight 301 kg, dim.mm.1380x620x1860h

SL-CPG900S/R

TECHNOCHEF - Combined display case for ice cream and pastry, temp. -15°-25°C/+4°+10°C, Mod.CPG900S/R

Combined display case for ice cream/pastry shop, 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, 4 display sides, 6 rectangular shelves + 6 rotating shelves, ventilated/static refrigeration, capacity liters. 848, V.230/1, Kw.0.70+0.54, dim.mm.1380x620x1860h

SL-CPS900V/R

Refrigerated Pastry Display Case 2 Doors, 4 display sides, 5 rectangular shelves + 6 rotating shelves

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 5 rectangular shelves + 6 rotating shelves, capacity 848 litres, temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw.0.54+0.54, Weight 301 Kg, dim.mm.1380x620x1860h

SL-CPS900R/R

Refrigerated Pastry Display Cabinet 2 Doors, 4 display sides, 12 rotating shelves, Curve Line

Refrigerated pastry display case with 2 doors, CURVE line, with 4 display sides, 12 rotating glass shelves, capacity 848 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54+0.54, weight 301 kg, dim.mm.1380x620x1860h

SL-CGL700S/S

TECHNOCHEF - Vetrina Freezer for Gelateria 2 Sizes, Temp.-15°-25°C, lt.742, Mod.CGL700S/S

Freezer-Freezer display case for ice cream parlor with 2 doors, temperature -15°/-25°C, static refrigeration, Curve Line, with 4 display sides, 12 square shelves measuring 460x460 mm, capacity 742 litres, V.230/1, Kw. 0.7+0.7, weight 270 kg, dim.mm.1180x620x1860h

SL-CPG900G2T/V

TECHNOCHEF - Combined display case for ice cream and pastry, temp.-15°-25°C/+4°+10°C, Mod.CPG900G2T/V

Combined display case for ice cream/pastry shop 2 doors, temp. -15°-25°C/+4°+10°C, Curve Line, with 4 display sides, 5 grilled shelves + 5 glass shelves, ventilated/static refrigeration, capacity lt.848, V.230/1, Kw.0.70+0.54, dim.mm.1380x620x1860h

SL-CGL900S/S

Vetrina Congelante per Pasticceria-Gelateria 2 Porte, 2 Vani, 2 Motori, Temp.-15°-25°C // -15°-25°C.

Freezer-Freezer display case for ice cream shop, capacity 848 litres, 2 doors, 2 temperatures. -15°/-25°C // -15°-25°C. , 2 separate compartments, 2 MOTORS, static, with 4 display sides, 12 shelves measuring 560x460 mm, V.230/1, Kw.0.7+0.7, Weight 287 Kg, dim.mm.1380x620x1860h

SL-CGL900G2T/G2T

Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, 848 lt, Mod.CGL900G2T/G2T

Multi-temperature display case from +5° to -20°C for 2-door pastry shops, ventilated refrigeration, Curve Line, with 4 display sides, 10 rectangular shelves measuring 565x445 mm, capacity 848 liters, V.230/1, Kw.0.75+0.75, weight 329 kg, dim.mm.1380x620x1860h

SL-CGL900G2T/R2T



Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, 848 lt, Mod.CGL900G2T/RG2T
Multi-temperature display case from +5° to -20°C for 2-door pastry shops, ventilated refrigeration, Curve Line, with 4 display sides, 5 gridded shelves + 5 rotating shelves, capacity 848 liters, V.230/1, Kw.0.75 +0.75, weight 329 kg, dim.mm.1380x620x1860h

SL-CGL900R2T/R2T



Refrigerated Pastry Display Case, Temp.+5°-20°C, 2 Doors, 848 lt, Mod.CGL900R2T/R2T
Multi-temperature display case from +5° to -20°C for pastry shops, 2 doors, ventilated refrigeration, Curve Line, with 4 display sides, 10 rotating glass shelves, capacity 848 liters, V.230/1, Kw.0.75+0,75, Weight 329 Kg, dim.mm.1380x620x1860h