



TECNOSERVICE'21 srl

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
BS-E9P2M/IND	ELECTRIC COOKER WITH 2 INDUCTION ZONES on OPEN CABINET, BERTOS MAXIMA 900 line, POWER INDUCTION Series, with 2 SQUARE ZONES measuring 270x270 mm, INDEPENDENT CONTROLS, 9 power levels, V.400/3+N, Kw.10.00, Weight 55 Kg, dim.mm.400x900x900h	

#### PROFESSIONAL DESCRIPTION

#### ELECTRIC COOKER with 2 INDUCTION ZONES on OPEN CABINET, MAXIMA 900 Line, POWER INDUCTION Series :

- **worktop and front and side panels in AISI 304 stainless steel** ;
- stainless steel interior;
- **6 mm thick glass ceramic top** ;
- **perfectly smooth surface** which guarantees quick cleaning, in just a few gestures and in a few minutes, without the use of aggressive detergents;
- **maximum energy saving** as the heating of the cooking area is activated only when the pan is in direct contact with the surface;
- energy saving is ensured by the **immediate achievement of the maximum temperature** inside the cooking containers whilst keeping the hob completely cold;
- **the high energy efficiency is given by the absence of heat dispersion** and consumption reduced by over 30%;
- **the heating zone self-regulates** based on the diameter of the pan;
- **immediate automatic interruption when the pan is removed from the hob** ;
- **digital indicator** that immediately indicates the **set power level, from 1 to 9** ;
- power regulation via robust high-precision control;
- **square areas measuring 270 x 270 mm and power 5 kW** ;
- **cooking zone power n°x Kw : 2 x 5** ;
- **2 year warranty** .

#### Accessories/Options :

- right/left door per compartment

CE mark

Made in Italy

#### TECHNICAL CARD

power supply Trifase

<b>Volts</b>	V 400/3 +N
<b>frequency (Hz)</b>	50
<b>net weight (Kg)</b>	55
<b>breadth (mm)</b>	400
<b>depth (mm)</b>	900
<b>height (mm)</b>	900



**MAXIMA 900**



n.	2
mm	270 x 270
kW	5



380-415 V3N ~ 50/60 Hz



TOT. kW	10
---------	----



Kg	55
----	----



**POWER INDUCTION**

5 kW	▶ 270x270 mm
5 kW	



