



| CODE                  | DESCRIPTION   | PRICE/DELIVERY  |
|-----------------------|---|---|
| <b>BS-E9F22-8M-BF</b> | ELECTRIC FRYER on MOBILE, BERTO'S, MAXIMA 900 Line, TURBO Series, 2 INDEPENDENT TANKS of 22+22 litres, BFLEX Electronic Controls, V.400/3+N, Kw.18+18, Weight 95 Kg, dim.mm. 800x900x900h | <b>€ 3.801,21</b><br><i>VAT excluded</i><br><b>Shipping to be calculated</b><br>Delivery from 15 to 25 days |

**PROFESSIONAL DESCRIPTION**

**ELECTRIC FRYER on MOBILE, MAXIMA 900 Line, TURBO Series, 2 INDEPENDENT TANKS of 22+22 lt , BFLEX ELECTRONIC CONTROLS:**

- **worktop and front and side panels in AISI 304 stainless steel ;**
- Incoloy **stainless steel heating elements** positioned directly inside the tank, which can be folded into a vertical position to facilitate cleaning operations;
- **safety device** for turning off the electricity supply with resistors in a vertical position;
- **temperature control via electronic control unit** with the following functions:
  - **temperature control from 100 to 190 °C ,**
  - **display of the set and working temperatures ,**
  - “ **melting** ” and maintenance **program at 100 °C** for the use of solid frying fats,
  - **self-diagnostics for any anomalies ;**
- **safety thermostat** with manual reset;
- **AISI 304 stainless steel tanks** with large rounded edges and a large cold area, beneath the heating elements, for settling residues;
- the top, with rounded edges, incorporates a slightly inclined surface for placing the baskets which facilitates the draining of the oil;
- **ball drain cock** , located inside the compartment, controlled by a handle with athermal grip, with steel collection tray;
- **24 month warranty .**

**Supplied:**  
◦ 2 unique baskets

**CE mark**  
**Made in Italy**

|                                  |            |
|----------------------------------|------------|
| <b>power supply</b>              | Trifase    |
| <b>Volts</b>                     | V 400/3 +N |
| <b>frequency (Hz)</b>            | 50         |
| <b>motor power capacity (Kw)</b> | 36,00      |
| <b>net weight (Kg)</b>           | 95         |
| <b>breadth (mm)</b>              | 800        |
| <b>depth (mm)</b>                | 900        |
| <b>height (mm)</b>               | 900        |



|  |             |                        |
|--|-------------|------------------------|
|  | L           | 22 + 22                |
|  | mm          | 306 x 460 x 295 h (x2) |
|  | mm          | 260 x 400 x 150 h (x2) |
|  | <b>kW</b>   | 18 x 2 (E9F22-8M-BF)   |
|  | <b>kW</b>   | 22 x 2 (E9F22-8MS-BF)  |
|  | <b>VOLT</b> | 380-415 V3N~ 50/60 Hz  |
|  | <b>Kg</b>   | 95                     |

