

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY	
TCF091-FRG040	Sanitizing refrigerator cabinet with ozone generator 1 door, Professional, capacity 900 lt, temperature 0°/+10°C, ventilated refrigeration, ECOLOGICAL gas R290, V.230/1, Kw.0.38, Weight 90 Kg, dimensions mm 790x1010x2090h	€ 2.917,28 VAT escluded Shipping to be calculed Delivery from 8 to 15 days	
PROFESSIONAL DESCRIPTION			

SANITIZING FRIDGE CABINET with OZONE GENERATOR, 1 Door, 900 lt., Temp.0/+10°C:

- Useful for preserving for a long time and sanitizing all foods that would normally be kept fresh, with the advantage of extending their shelf life;
- Equipped with a fully automated digital control device meeting Industry 4.0 requirements;
- Time controlled ozonator;
- OZONE used in small quantities (1 min. every 20 min.) extends the shelf life of the products and keeps their quality intact;
- OZONE generator via electric generator with maximum production of 250 MG/H (air powered) operation via ON/OFF time setting;
- The wardrobe is equipped with :
 - Cooling element;
 - High-tech Ozone Generator :
 - Forced ventilation, to guarantee uniformity of the quality of Ozone inside the cell,
 - · Digital instrument that controls the ozone temperature, times and safety of any door opening.
- The system records all events and programs and is interconnected following the industry 4.0 criterion. To ensure proper functioning of the system it is necessary to connect the device to the internet;
- Product that falls within the TAX CREDIT (DL 23/2020) Tax credit of 50% of sanitation costs up to a maximum of 20,000 euros (waiting for officialisation).

TECHNICAL DATA

- Made of AISI 304 stainless steel;
- Number of doors 1:
- Suitable for containing 600x400 mm grids;
- Racks with 62 mm pitch;
- Capacity 900 liters;
- Operating temperature 0°/+10° C;
- Insulation 75 mm;
- Ventilated refrigeration;
- Hot gas defrost;
- ECOLOGICAL refrigerant gas R290;
- Climate class 5;
- Digital thermostat;
- Ventilation stop as standard;
- Ambient temperature of use from +18° to +25°C;
- Automatic closing door as standard;
- Standard lock;
- o Optional internal lighting;
- o Adjustable feet as standard;
- Single-phase power supply;
- Power 380W;
- o Internal dimensions 640x850x1480h mm
- External dimensions 790x1010x2090h mm.

Supplied:

- o n. 8 x grill guides
- o n. 4 grids 600x400 mm

CE MARK MADE IN ITALY

TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,38	
net weight (Kg)	90	
breadth (mm)	790	
depth (mm)	1010	
height (mm)	2090	