



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TCF091-ARM070</b>	Sanitizing cabinet with 1 door ozone generator, capacity 200 lt, V.230/1, Watt 65, dimensions mm 660x600x1000h	<b>€ 968,26</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 8 to 15 days
PROFESSIONAL DESCRIPTION		

**NEUTRAL SANITIZING CABINET with OZONE GENERATOR , 1 Door , 200 lt .:**

- **Cabinet for SANITIZING fruit, vegetables, kitchen utensils, work utensils, office objects, clothing, shoes, personal linen, bedroom linen, objects in general ;**
- **Operation with sensor** , when the door is closed the sanitization cycle begins which must be confirmed by the user;
- If confirmed, an orange LED lights up and remains for the entire duration of the cycle, including the Ozone degradation time;
- The green LED when lit indicates that the system is powered;
- **The program is preset fixed in three phases :**
  - **Ozone creation phase** ( 3 Min.);
  - **Ozone reaction phase** (15 Min.);
  - **Ozone decay phase** (30 Min.\*) (\*Time may vary depending on: products, contamination, humidity, quantity)
- **If the door is opened during sanitisation, the cycle stops immediately** . The closure is hermetically guaranteed by a perimeter gasket;
- If it is used more than once a day, especially in narrow and unventilated environments, on request as an optional, the cabinet can be equipped with an extractor that allows the gases to escape to a centralized filtering system, otherwise opt for the installation of an internal recirculating catalyst system;
- The cabinet should never be opened until the cycle is finished,
- **The SANITIZING cabinet also boasts the following features :**
  - **high-tech ozone generator** ,
  - **body entirely insulated in polyurethane thickness from 40 to 50 mm** ,
  - **automatic door closing with magnetic seal** to ensure that the internal compartment is airtight, a necessary condition for safety,
  - **possibility of removing odors and sanitizing** ;
- **Product that could fall within the TAX CREDIT (DL 23/2020) defined at 50% of the sanitation costs up to a maximum of 20,000 euros** (awaiting officialisation);
- The cabinets are not supplied with plugs;
- **On request, possibility of external coloring White or Black - Optional** .

**TECHNICAL DATA :**

- Capacity 200 litres
- Grids n.2
- Power consumption 65 W
- Dimensions mm (WxDxH) 660x600x1000h

**Accessories/Options :**

- Activated carbon filter system for intensive use
- Activated carbon replacement filter, lasts 6 months
- Stainless steel slotted surface mm. 470x490
- External white or black color surcharge

**CE MARK****MADE IN ITALY****TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,065
<b>breadth (mm)</b>	660
<b>depth (mm)</b>	600
<b>height (mm)</b>	1000

