



TECNOSERVICE'21 srl
 by Tinti Sergio
 Via Carlo Pisacane, 134
 61032 Fano (PU) Italy
 P.IVA IT0200411413

Tel. +39 0721 805911
 FAX +39 0721 809794
 e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TH-MATICMANU8	Semi-automatic cabinet purifier/softener, manual activation of regeneration via button, max flow rate 500 l/h, dim.mm.245x340x485h	€ 221,04 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days

PROFESSIONAL DESCRIPTION

SEMI-AUTOMATIC SOFTENER CABIN, with MANUAL ACTIVATION of REGENERATION THROUGH A BUTTON :

- **Max flow rate** : 500 LT/H
- **Min Pressure** : 1.5 ATE
- **Max pressure** : 7 ATE
- **Min - max water temperature** : 2 - 35 °C
- **Inlet - Outlet connection** : 3/8 M
- **Drain Fitting** : HOSE HOLDER DIAM.14 MM
- **Regeneration duration** : 22' MINUTES
- **Quantity of salt consumed during Regeneration** : 0.8 KG.
- **Hardness Mixing System** : Yes

Limestone is mainly responsible for all the problems of blockage and damage to pipes , taps , coils , boilers and a significant increase in energy consumption which is often not noticed. The advantages deriving from the use of softened water are concrete and tangible .

The softener mod. MATIC MANU 8 has been designed to meet the needs of those who supply equipment for bars , large kitchens , restaurants , hotels and manufacturers or traders of coffee machines , roasters, ovens and dishwashers .

The main features of this softener are its **very small size** , its **compactness** , **suitable for installation in minimum spaces** and the **ease of carrying out the regeneration** which, combined with an application that can be downloaded on APPLE and ANDROID, allows the regeneration to be carried out correctly and within the times indicated, without waste of time.

IDEAL FOR THE CONNECTION OF :

Ideal for convection ovens

Or:

N.1 Coffee machine 2 groups

CE MARK

TECHNICAL CARD

breadth (mm) 245

depth (mm)	340
-------------------	-----

height (mm)	485
--------------------	-----