



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>MZ-GRVF290</b>	1 glass door freezer-freezer cabinet, 700 lt capacity, ENERGY SAVING - HIGH THICKNESS, temp. -10°/-20°C, with PRINTED GUIDES, ventilated, ECOLOGICAL gas R290, Gastro-norm 2/1, with light and key, V 230/1, Kw.0.45, dim.mm.690x830x2050h	<b>€ 3.261,13</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 8 to 15 days
<b>PROFESSIONAL DESCRIPTION</b>		

**FREEZER-FREEZER CABINET 1 GLASS DOOR, capacity 700 litres, temperature -10°/-20°C, ECOLOGICAL gas R290:**

- **exterior and interior** in **AISI 304 stainless steel** , bottom and back in galvanized steel;
- suitable for containing **grills** or **Gastro-Norm 2/1 containers (mm.530x650)** ;
- **guides printed on the sides;**
- **ventilated refrigeration;**
- **insulation in CFC-free polyurethane** injected at high pressure with **a density of 42 kg/m3;**
- **insulation thickness 80 mm** for greater insulation;
- **built-in refrigeration unit** operating with **ECOLOGICAL R290 gas** , **Zanussi compressor** ;
- **evaporator positioned retractably** so as to have **maximum available space** ;
- engine compartment with insulated sides;
- **electronic temperature control** with **digital thermometer** - thermostat;
- **internal light and key lock;**
- **automatic defrost with electric resistance and automatic control of the defrost temperature** ;
- **automatic evaporation** of condensation water;
- **anti-corrosion** treated evaporator;
- **door with return spring** and reversible;
- door seal removable without tools;
- bottom with **rounded corners** ;
- feet in **AISI 304 stainless steel adjustable in height** (110/170 mm);

**Supplied :**

- - **n. 23 Pairs of Molded Rails, Lockable, Light .**

**CE MARK  
MADE IN ITALY**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,45
<b>breadth (mm)</b>	690
<b>depth (mm)</b>	830
<b>height (mm)</b>	2050