



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TD-ATT02</b>	TEMPERATURE BLAST CHILLER-FREEZER with 340x363x270h mm CHAMBER, for 3 Gastro-Norm 2/3 GRILLS/TRANS, needle probe, POSITIVE CYCLE yield +70°/+3° Kg.9, NEGATIVE CYCLE yield +70°/-40 ° Kg.7, V.230/1, Kw.0.52, Weight 45Kg, dim.mm.658x630x420h	<b>€ 1.044,87</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 8 to 15 days

PROFESSIONAL DESCRIPTION

**SUPER POWERFUL and SUPER COMPACT BLAST CHILLER with GUIDES for 3 Gastro-Norm 2/3 GRILLS/TRAINS (mm.354x325), TECNODOM brand :**

- **Internal and external in Stainless Steel** , with the exception of the external bottom in Galvanized Steel;
- Rounded internal corners;
- Insulation in CFC-free polyurethane, injected at high pressure;
- Removable upper shelf, door with automatic closing and magnetic seal;
- **Front panel with electronic control card with chamber probe and core needle probe ;**
- **Ventilated refrigeration** with air agitator;
- Easily removable and tropicalized refrigeration unit as standard (ambient temperature +43°C and relative humidity of 65%);
- **Timed evaporator defrost** , at the end of the cycle, and lower condensation water containment tray;
- **Cycles can be set with core probe +3°C and -18°C** , or by time;
- The power is guaranteed by a unit capable of bringing **a temperature of -40°C to the chamber in a few minutes** ;
- Guides suitable for holding **3 standard GN 2/3 grids or trays** (354x325mm);
- **Pitch between guides 80 mm** ;
- **Chamber dimensions mm 340x363x270h** ;
- Yield: **positive cycle +70°+3°C -- 9 kg** ,
- Yield: **negative cycle +70°- 40°C -- 7 kg** ;
- **Digital control panel** allows you to set various parameters to meet any need;
- **Insulation thickness 60 mm** ;
- Thanks to its small size, it can also be placed on a workbench or refrigerated;
- **Height-adjustable stainless steel feet** (60/90 H mm).

**NB: Trays and grills NOT INCLUDED**

**Supplied :**

- Chamber probe
- Needle probe
- 3 pairs of guides

**Accessories/Options :**

- GN 2/3 aluminum tray (354x325 mm)


**CE MARK**

**MADE IN ITALY**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,52
<b>net weight (Kg)</b>	45
<b>gross weight (Kg)</b>	56
<b>breadth (mm)</b>	658
<b>depth (mm)</b>	630
<b>height (mm)</b>	420

**TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<p><b>TD-VXAB000001</b></p> 	<p><b>GN 2/3 ALUMINUM TRAY</b> GN 2/3 aluminum tray (mm 354x325), for mod.ATT02</p>	<p><b>€ 33,11</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days</p>



