



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TCF133-SF-BECO-95	Countertop pastry sheeter with 95x50 cm BELTS-MATCHES, MANUAL CONTROLS, mm-long folding tables. 950, ROLLING ROLLERS of 500 mm, ROLLER OPENING from: 0 to 40 mm, Weight 99 kg, kw 0.55, dim. open mm. 2000x870x600h	€ 3.154,85 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days

PROFESSIONAL DESCRIPTION

PASTRY SHEETER with 95x50 cm BELTS (Belts), Bench Version, Professional, Roller opening from 0 to 40 mm, Upward Folding Tables 950 mm long:

- **Designed for extremely small spaces** , thanks **to the absence of an undercounter** and the stainless steel puff pastry extension;
- Designed and engineered to ensure **extremely easy and functional use**, in full compliance with international safety standards;
- **Reliable, solid and efficient structure** , it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;
- Shoulders and covers in cast aluminium;
- Use of the **handle to adjust the thickness**;
- Possibility of working **any type of pasta , up to very thin thicknesses**;
- Micrometric adjustment of the cylinder descent with aluminum handle;
-
- Hard chrome plated **rolling cylinders , ground and polished**;
- **cylinder diameter: Ø 6 cm;**
cylinder opening: from 0 to 4 cm;
cylinder width: 50 cm;
-
- **Movement of the BELTS (belts) via joystick ;**
- **1 speed of the BELTS** (with differentiated speed between the entry belt and the exit belt);
- **Stainless steel protection grills** with **safety microswitch**;
- **Tables that fold upwards** , so as to reduce the overall dimensions when the machine is at rest;
- Non-removable table system;
- **Working dimensions** : 2000 X 870 X 600h mm;
- **Dimensions at rest** : 850 X 870 X 990 mm;
-
- **Low voltage and dual control electrical system** (manual and pedal);
- **Accident prevention guards** , connected to the electrical system via limit switches;

Optional:

- Also available with single-phase motor;
- **2-speed motor** , with differentiated speed between the entry belt and the exit belt;

CE MARK
Made in Italy

TECHNICAL CARD

power supply	Trifase
Volts	V 400/3
frequency (Hz)	50
motor power capacity (Kw)	0,55
net weight (Kg)	94
gross weight (Kg)	96
breadth (mm)	2000
depth (mm)	870
height (mm)	600