

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973 $\,$



CODE	DESCRIPTION	PRICE/DELIVERY
TCF133-SF-500-71	Professional pastry sheeter with 710x500 mm BELTS-MATCHES equipped with UNDERPLATE for FLOUR and PASTRY COLLECTOR, MM ROLLING rollers. 500 adjustable from: 0 to 35 mm, weight 150 kg, kw 0.75, dim. open mm. 1800x880x1100h	€ 3.644,94 VAT escluded Shipping to be calculed Delivery from 4 to 9 days
	PROFESSIONAL PESSENTION	

PROFESSIONAL DESCRIPTION

Professional floor-standing PASTRY SHEETER, with 710x500 mm BELTS-MATS with UNDERPLATE for FLOUR collection and PASTRY COLLECTION, Roller opening from: 0 to 35 mm, Folding TABLES 710 mm long:

- Designed and engineered to ensure extremely easy use and functional, in full compliance with safety standards international;
- Reliable, solid and efficient structure, it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;
- Shoulders and covers in cast aluminium;
- Possibility of working any type of pasta, up to very thin thicknesses;
- Hard chrome plated rolling cylinders , ground and polished;
- Micrometric adjustment of the cylinder opening with aluminum handle ;
- ∘ cylinder diameter: Ø 6 cm;
- cylinder opening: from 0 to 3.5 cm;
- o cylinder length: 50 cm;
- $\circ\,$ Paste scraper on easily removable cylinders , for easy and effective cleaning;
- Movement of the BELTS CARPETS via pedal control;
- Variable speed conveyor belts-belts to avoid wrinkles in the pastry;
- Stainless steel protection grills with safety microswitch;
- Shielded bearings to avoid flour infiltration;
- Tables that fold upwards , so as to reduce the overall dimensions when the machine is at rest;
- Non-removable table system with stainless steel under-top for FLOUR collection and Dough collector;
- Mounted on wheels to facilitate movement;
- Working dimensions: 1800 x 880 x 1100h mm;
- o Dimensions when at rest: 600 x 880 x 1460h mm;
- Low voltage and dual control electrical system (manual and pedal);
- Accident prevention guards , connected to the electrical system via limit switches;

Optional:

- Also available with single-phase motor;
- 2-speed motor, with differentiated speed between the entry belt and the exit belt;

CE MARK Made in Italy

TECHNICAL CARD		
power supply	Trifase	
Volts	V 400/3	
frequency (Hz)	50	
motor power capacity (Kw)	0,75	
net weight (Kg)	150	
breadth (mm)	1800	
depth (mm)	880	
height (mm)	1100	