

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973  $\,$ 



CODE	DESCRIPTION	PRICE/DELIVERY
TCF133-SF-E500-120	Professional pastry sheeter with 1200x500 mm BELTS-MATS equipped with UNDERPLATE for FLOUR and PASTRY COLLECTOR, REMOVABLE tables, 500 mm ROLLING ROLLERS, adjustable from 0 to 35 mm, Weight 180 Kg, 0.75 kW, open size mm. 2800x930x1100h	€ 4.229,86  VAT escluded  Shipping to be calculed  Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

Professional floor-standing PASTRY SHEETER, with 1200x500 mm BELTS-MATS, with UNDERCOUNTER for FLOUR collection and PASTRY COLLECTION, Roller opening from: 0 to 35 mm, Foldable and EXTRACTABLE TABLES 1200 mm long:

• Designed and engineered to ensure extremely easy and functional use, in full compliance with international safety standards;

• Reliable, solid and efficient structure, it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;

• Shoulders and covers in cast aluminium;

• Possibility of working any type of pasta , up to very thin thicknesses;

- $\circ~$  Hard chrome plated rolling cylinders , ground and polished;
- Micrometric adjustment of the cylinder opening with aluminum handle;
- cylinder diameter: Ø 6 cm;
- cylinder opening: from 0 to 3.5 cm;
- cylinder length: 50 cm;
- Paste scraper on easily removable cylinders , for easy and effective cleaning;
- Movement of the BELTS-MATCHES via pedal control;
- Variable speed conveyor belts-belts to avoid wrinkles in the pastry;
- Stainless steel protection grills with safety microswitch;
- Shielded bearings to avoid flour infiltration;
- Tables that fold upwards , so as to reduce the overall dimensions when the machine is at rest;
- · Removable Table System with Stainless Steel Undertop for FLOUR Collection and Pasta Collector;
- Mounted on wheels to facilitate movement;
- 0
- $\circ~$  Working dimensions : 2800 x 930 x 1100h mm;
- o Dimensions when at rest: 990 x 930 x 1900h mm;
- Low voltage and dual control electrical system (manual and pedal);
- Accident prevention guards , connected to the electrical system via limit switches;

## **Optional:**

0

- Also available with single-phase motor;
- 2-speed motor, with differentiated speed between the entry belt and the exit belt;

## CE MARK Made in Italy

TECHNICAL CARD		
power supply	Trifase	
Volts	V 400/3	
frequency (Hz)	50	
motor power capacity (Kw)	0,75	
net weight (Kg)	180	
breadth (mm)	2800	
depth (mm)	930	
height (mm)	1100	