



TECNOSERVICE'21 srl
by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

1-door PROOFING CABINET, capacity 700 liters (71FL) or 900 liters (91FL), temperature -6/+40°C with cold, heat and holding function

- The retarder-prover cabinets are designed to **perform complete and customizable retarder/prover cycles** .
- Through **4.0 technology, digital management** of various functions is possible, **even remotely**

Main characteristics:

- monocoque with **60 mm insulation** (75 mm for the 900 lt) with HFO expanded polyurethane, which has a GWP level 0
- cell operating temperature **-6° + 40°C**
- device with **fully automated digital control** meeting **Industry 4.0 requirements**

The retarder-prover cabinets can perform **multiple functions** including:

- management of **cooling, heating** , and **maintenance** ;
- management and operation via **temperature reading probes** : evaporator, suction cell;
- **cold/warm/hold** function;
- **complete retarding/rising cycles** can be performed by setting times and temperature and ventilation characteristics;
- It can also be used for **preserving, defrosting, drying** , etc

OPTIONALS:
GLASS DOOR
CE mark

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50

AVAILABLE MODELS

IB-71FL



Retarder-prover cabinet, cold, warm and holding function, temperature -6° / +40°C, mod. 71FL

1-door retarder-prover cabinet, 700 lt, temp. -6°/+40°C, stainless steel structure, touch screen control panel, ventilated refrigeration, V. 230/1, kw 0.52, dim. mm 720x800x2020h

€ 2.953,92

VAT excluded
Shipping to be calculated

Delivery

IB-91FL



Retarder-prover cabinet, cold, warm and holding function, temperature -6° / +40°C, mod. 91FL

1-door retarder-prover cabinet, 900 lt, temp. -6°/+40°C, stainless steel structure, touch screen control panel, ventilated refrigeration, V. 230/1, kw 0.52, dim. mm 790x1010x2090h

€ 3.490,59

VAT excluded
Shipping to be calculated

Delivery



