



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
HT-HA125	Infrared RADIANT HEATING LAMP for rooms, adjustable with remote control, 4 power levels, adjustable thermostat V.230/1, kw 2.4, cm 97x8x16h	€ 148,45 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days

PROFESSIONAL DESCRIPTION

Infrared (FIR) heating lamp for rooms up to 25 m² with remote control

- **Infrared tube** with **high efficiency carbon fiber** heating element
- **Homogeneous diffusion of heat** by radiation.
- **Long wave infrared rays (FIR)** guarantee **maximum comfort**
- **4 power levels** : 10%, 40%, 60%, 100%
- Heated area **up to 25 m²**
- **Thermostat adjustable** from 5 to 45 °C
- Temperature setting in **°C or °F**
- Useful life of the infrared tube: **approximately 5000 hours of operation** .
- **Quick and easy** infrared tube **replacement**

Functions and features

- **“Open Window Detection” function** : the device automatically turns off if the ambient temperature drops by more than 3°C in 2 minutes
- **“Smart Heating” function** : the radiator automatically adapts the heating power based on the ambient temperature, this allows for greater efficiency in using the radiator.
- **Timer function** : switch-off timer programmable up to 24 hours
- **LED display**
- **IP65 protection**
- **Child safety lock**
- **Overload protection**
- **Remote control included** : works with 1 CR2025 3V battery and 2 AAA 1.5V batteries (not included). Remote control sensitivity: MAX 6 m
- Cable length 1.7 m
- Mounting: ceiling or wall installation at the desired angle, screws and brackets included.
- Minimum distance on the sides: 50 cm
- Minimum distance from the ceiling: 50 cm
- Minimum distance from the floor: 180 cm

CE mark

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	5060

motor power capacity (Kw)	2,4
net weight (Kg)	6
gross weight (Kg)	10
breadth (mm)	970
depth (mm)	80
height (mm)	160