



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



**Nota:** Vedi nell'immagine aggiuntiva i colori disponibili

PROFESSIONAL DESCRIPTION

**CELLAR-CASES for WINE, Capacity 24 Horizontal Bottles, STATIC or VENTILATED REFRIGERATION, suitable for WHITE or RED WINES, SLIM Line, 36 cm deep:**

- **aluminum structure** ,
- interior in Aluminium,
- sliding doors, sides and top in **double glazing** ,
- **ECOLGICO** refrigeration **unit** with GAS R 600a
- **digital thermoregulator** from: **+4°+16°C** ;
- **automatic defrost** , automatic condensation evaporation,
- **inverter compressor** ,
- **innovative refrigeration system based on the positioning of the cooling coil inside the refrigerated compartment behind the rear panel which guarantees better storage conditions** ,
- **SLIDING glass DOORS on 1 FRONT** ,
- **anti-fog system doors** ;
- **natural white LED lighting on the uprights** ,
- key **lock** ,
- **anti-vibration system** ,
- Ambient Temperature: +25°, MAX for WHITE WINES
- Ambient Temperature: +30°, MAX for RED WINES

**4 POSSIBILITIES OF USE CONFIGURABLE by the Customer**

- **STATIC MULTI-TEMPERATURE from +4° to +16°C for WHITE and RED wines** ,
- **STATIC MULTI-TEMPERATURE from +14° to +20°C for ROSS I wines** ,
- **VENTILATED for RED Wines with adjustable temperature from +14° to + 16° C** ,
- **VENTILATED for WHITE wines with adjustable temperature from +4° to +6° C**;

**Possible EQUIPMENTS, to be selected at the TIME of the Order in the PRODUCT SHEET .**

**- FRAME in RAW MDF , - MATT WHITE RAL-9010, - MATT BLACK RAL-9005, - GOLD VO1, SILVER VO2, - RAL 20 COLORS MATT LACQUERED, RAL 100 COLORS GLOSS LACQUERED**

**OPTIONAL/ACCESSORIES:**

- **Colored LED lighting on the uprights with remote control**

**CE mark**  
**Made in Italy**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>net weight (Kg)</b>	59
<b>breadth (mm)</b>	860
<b>depth (mm)</b>	362
<b>height (mm)</b>	897

**AVAILABLE MODELS**

**EO-TV-H20-M01**



**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm Depth, Version with RAW MDF WOOD FRAME**

WINE CASE with FRAME in RAW MDF WOOD, 3 GLASS SIDES, HORIZONTAL cap.24 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.412,09**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days

**EO-TV-H20-RAL9010**



**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm deep, Version with WOODEN FRAME in MATT WHITE color**

WINE CABINET with FRAME in MATT WHITE WOOD, 3 GLASS SIDES, HORIZONTAL cap.24 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.447,26**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days

**EO-TV-H20-RAL9005**

**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm deep, Version with WOODEN FRAME in MATT BLACK color**  
 WINE CABINET with FRAME in MATT BLACK WOOD, 3 GLASS SIDES, HORIZONTAL cap.24 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.447,26**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days

**EO-TV-H20-RAL20**

**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm deep, Version with WOODEN FRAME in RAL20 colors**  
 WINE CABINET with WOODEN FRAME in RAL20 colours, 3 GLASS SIDES, cap.24 HORIZONTAL bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.799,03**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days

**EO-TV-H20-V01**

**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm deep, Version with GOLD painted WOODEN FRAME**  
 WINE CASE with GOLD painted WOODEN FRAME, 3 GLASS SIDES, HORIZONTAL cap.24 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.799,03**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days

**EO-TV-H20-V02**

**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm deep, Version with SILVER painted WOODEN FRAME**  
 WINE CASE with SILVER painted WOODEN FRAME, 3 GLASS SIDES, HORIZONTAL cap.24 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V .230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.799,03**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days


**EO-TV-H20-RAL100**

**WINE CASE, 24 Bottles, Doors on 1 Front, 3 Glass Sides, SLIM Line, 36 cm deep, Version with WOODEN FRAME in RAL100 colors**  
 WINE CASE with WOODEN FRAME in RAL100 colours, 3 GLASS SIDES, HORIZONTAL cap.24 bottles, STATIC or VENTILATED cold, temp.+4°/+16°C, for WHITE or RED WINES, doors on 1 front, V.230/1, Kw.0,15, Weight 59 Kg, dim.mm.860x362x897h

**€ 3.799,03**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days





TV-H20

+



T2-H-\*



POSSIBILI IMPOSTAZIONI • POSSIBLE SETTINGS • CHOIX DE RÉGLAGE

Statico <i>Static · Statique</i>		Ventilato <i>Ventilated · Ventilée</i>	
1	2	3	4

Le temperature riportate sono indicative e possono variare di [+ -] 2 °C. L'utente può impostare la temperatura da +4 °C a +18 °C.  
Reported temperatures are approximate and may vary by [+ -] 2 °C. User-controlled temperature +4 °C to +18 °C.  
Les températures indiquées sont approximatives et peuvent varier de [+ -] 2 °C. L'utilisateur peut régler la température de +4 °C à +18 °C.



COLORI CORNICE • FRAMES COLOURS • COULEURS DU CADRE



T2-H-\*

MDF non verniciato • Unfinished MDF • MDF non peinte



MQ1  
MDF non verniciato  
unfinished MDF  
MDF non peinte

Verniciatura a liquido • Liquid paint finish • Laquage par peinture liquide



RAL 9010  
bianco opaco (20 gloss)  
matte white (20 gloss)  
blanc mat (20 gloss)



RAL 9005  
nero opaco (20 gloss)  
matte black (20 gloss)  
noir mat (20 gloss)



VD1  
verniciato oro  
gold paint  
peinture or



VD2  
verniciato argento  
silver paint  
peinture argent




RAL  
opaco 20 gloss - lucido 100 gloss  
matte 20 gloss - glossy 100 gloss  
mat 20 gloss - brillant 100 gloss



UNITÀ REFRIGERANTE INTEGRATA • SELF-CONTAINED REFRIGERATING UNIT • UNITÉ RÉFRIGÉRANTE INTÉGRÉE

IMPIANTO A REFRIGERAZIONE POSTERIORE - CONDENSAZIONE STATICA  
REAR COOLING SYSTEM - STATIC CONDENSATION  
SYSTÈME DE RÉFRIGÉRATION ARRIÈRE - CONDENSATION STATIQUE









La serpentina di raffreddamento ① e le ventole di aereazione interna ② sono posizionate all'interno del vano refrigerato dietro il pannello posteriore in alluminio. Il compressore ad inverter ③ e la vasca per l'evaporazione della condensa ④ sono inseriti nella base inferiore. Il condensatore statico ⑤ è installato nel retro della vetrina. Il raffreddamento del condensatore avviene per convezione senza l'ausilio di ventole. L'aria ambiente passa sotto la base e sale nello spazio tra il retro della vetrina ed il muro, si riscalda ed esce dall'alto.

The cooling coil ① and the internal aeration fans ② are placed inside the refrigerated compartment, behind the aluminum back panel. The inverter compressor ③ and the evaporation pan ④ are placed in the lower base. The static condenser ⑤ is installed in the back of the cabinet. The condenser cools down due to convection without the use of fans. Ambient air comes through under the base and rises in the gap between the back of the cabinet and the wall, gets warm and exits from the top.

Le serpentin de refroidissement ① et les ventilateurs internes ② sont positionnés à l'intérieur du compartiment réfrigéré derrière le panneau du fond en aluminium. Le compresseur onduleur inverter ③ et le réservoir d'évaporateur de condense ④ sont insérés dans la base inférieure. Le condensateur statique ⑤ est installé à l'arrière de la vitrine. Le refroidissement du condensateur se fait par convection sans l'aide de ventilateurs. L'air passe sous la base et s'élève dans l'espace entre l'arrière de la vitrine et le mur, il se réchauffe et s'échappe vers l'hauf.



-  Accende e spegne lo strumento • Turn on and off the appliance • Allume et éteint l'appareil
-  Accende e spegne la luce • Turn on and off the light • Allume et éteint l'éclairage
- SET** Per visualizzare/modificare Set point • View/change the set point • Pour afficher/changer le point de consigne
-  Per avviare sbrinatorio manuale • Start the manual defrost cycle • Pour lancer le dégivrage manuel
-  Per diminuire la temperatura • Decrease the temperature • Pour diminuer la température
-  Per aumentare la temperatura • Raise temperature • Pour augmenter la température
- FLUX** Per attivare resistenza guide • Switch on rails heating • Pour activer le rechauffage du cadre des rails
-  Per attivare ventole interne • Switch on inside fans • Pour activer les ventilateurs intérieurs



ILLUMINAZIONE  
A LED