



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
LH-ICOOL40W	Refrigerated wine cellar, 1 glass door, capacity 126 bottles, temperature +4°C/+18°C +16°C/+10°C/+5°C, static refrigeration with fan, LED lighting, V.230/1, Kw.0.23, Weight 67 Kg, dim.mm.600x650x1850h	€ 713,02 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

REFRIGERATED WINE CELLAR, 1 glass door, capacity 126 bottles of 0.75 litres :

- **External surface in pre-painted sheet metal with anti-corrosion treatment ;**
- Internal surface in ABS;
- **Frameless infinity door ;**
- **Static refrigeration with on/off fan ;**
- **Temperature: +16 °C /+10 °C /+5 °C fan OFF | +4 °C / +18 °C fan ON ;**
- Climate Class: 4;
- **R600A refrigerant ;**
- Energy Consumption kWh/24H: 2.84;
- Net-Gross Volume: Lt. 342 / 382;
- **Capacity 126 bottles of 0.75 liters** (indicative and variable data depending on the different packaging) ;
- **Electronic thermostat ;**
- **Insulation thickness 40 mm ;**
- **Automatic defrost when compressor is stopped + Manual ;**
- **Lighting: 2 vertical LEDs ;**
- Automatic door closing;
- Key and lock;
- Door reversibility;
- Shelves: N° 5 - 513x410 mm;
- 2 Feet, 2 Wheels.

Accessories/Options :

- Wooden shelves
- Sub Zero (Temp. -2°C/+2°C) / Digital Thermometer - Electronic Regulator

CE mark

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,23
net weight (Kg)	67
gross weight (Kg)	79
breadth (mm)	600
depth (mm)	650
height (mm)	1850



Porta a sfioro senza cornice **ICOOL 40 W**
Full glass frameless door **ICOOL 40 W**



Interno in ABS termoplastico
Thermoformed ABS inner liner



Mensole in legno - **Optional**
Wooden shelves - **Optional**



TECHNO CHEF



Dimensioni mm / Dimensions mm

Modello / Model	CLW 372 VG	ICOOL 40 W
Dimensioni Esterne (LxPxH) External Dimensions (WxDxH)	600 x 624 x 1863	600 x 650 x 1850
Dimensioni Imballo (LxPxH) Packaging Dimensions (WxDxH)	660 x 710 x 1990	660 x 710 x 1990
Dimensioni Interne mm / Inner Dimensions mm		
A - Larghezza / Width	522	522
B - Profondità / Depth	449	449
C - Altezza / Height	1557	1557
D - Profondità Min. / Min. Depth	179	179
E - Altezza Min. / Min. Height	1337	1337
Dimensioni Personalizzazione (LxH) mm / Sticker Dimensions (WxH) mm		
Vetro / Glass	503 x 1544	503 x 1544



Capienza / Capacity

Modello / Model	CLW 372 VG	ICOOL 40 W
Btg cl. 75 / Btl cl. 75	126	126

Dati indicativi e variabili a seconda dei diversi packaging
Variable data depending on the different packaging