



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-M-GN1410BTG-FC</b>	Professional Freezer-Freezer Cabinet, 2 Glass Doors, with Monobloc, Plug-in System, Ventilated, 1300 lt, Temp.-18°/-22°C, GN 2/1, Ecological in Class E, Gas R290, V. 230/1, Kw.0,815, Weight 206 Kg, dim.mm.1480x830x2010h	<p><b>€ 1.830,69</b>  <i>VAT excluded</i>  <b>Shipping to be calculated</b>  <b>Delivery</b> from 8 to 15 days</p>
<b>PROFESSIONAL DESCRIPTION</b>		

**FREEZER-FREEZER CABINET 2 GLASS DOORS , Professional Line, It.1300, Ventilated, GN 2/1, Temp.-18°/-22°C, with monobloc, plug-in system, Class E :**

- **made of AISI 201 stainless steel ;**
- **ventilated refrigeration ;**
- **Monobloc refrigeration unit ;**
- **refrigeration unit with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- silent motor;
- **monobloc protected by stainless steel sheet ;**
- **temperature -18°/-22°C ;**
- **electronic temperature control with digital thermostat ;**
- **energy class C ;**
- **ecological refrigerant gas R290 ;**
- maximum ambient temperature: +32°C;
- maximum ambient humidity: 60%HR;
- electric resistance around the door frame to eliminate condensation;
- **insulation thickness 60 mm ;**
- **automatic defrost ;**
- **electronic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- door with return spring and reversible;
- door lock with key;
- door seal removable without tools;
- internal LED light;
- bottom with rounded corners;
- external bottom and back panels in galvanized sheet metal;
- Height-adjustable feet.

**Supplied :**

- 6 GN 2/1 grills
- 6 pairs of guides

**CE MARK**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,815
<b>net weight (Kg)</b>	206
<b>gross weight (Kg)</b>	227
<b>breadth (mm)</b>	1480
<b>depth (mm)</b>	830
<b>height (mm)</b>	2010



M-GN1410BTG-FC



**7541** kWh/annum

  
**1.45** m<sup>2</sup>

 **-12°C**  
**-15°C**

8102/21/06