

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



FC-M-GN650TN-FC

1 door refrigerated cabinet, with monobloc, plug-in cystem # 650 Temp +0°/+8°C FCOLOGICAL in Class

1 door refrigerated cabinet, with monobloc, plug-in system, lt.650, Temp.+0°/+8°C, ECOLOGICAL in Class D, Gas R290, Ventilated, GN 2/1, V.230/1, Kw. 0.305, weight 108 kg, dim.mm.740x830x2010h

VAT escluded
Shipping to be calculed

Delivery from 8 to 15 days

PROFESSIONAL DESCRIPTION

1-DOOR REFRIGERATOR, WITH MONOBLOC, PLUG-IN SYSTEM, capacity 650 litres, temperature $+0^{\circ}/+8^{\circ}$ C, ECOLOGICAL in Class D:

- made of AISI 201 stainless steel;
- Monobloc refrigeration unit;
- refrigeration unit with plug-in system characterized by easy and immediate installation or possible removal/replacement;
- o quieter engine;
- monobloc protected by stainless steel sheet;
- cabinet with insulation thickness 60 mm;
- chamber bottom with rounded corners;
- external bottom panels in galvanized sheet metal;
- interior light;
- door with return spring and reversible;
- door locking with key;
- door seal removable without tools;
- suitable for containing Gastronorm 2/1 grills or containers (650x530 mm);
- ventilated refrigeration;
- operating temperature +0°/+8°C;
- electronic temperature control with digital thermostat;
- anti-corrosion treated evaporator;
- ECOLOGICAL Refrigerating Group with R290 gas;
- engine compartment with insulated sides;
- \circ electric resistance around the door frame to eliminate condensation;
- automatic defrost;
- automatic evaporation of condensation water;
- maximum ambient temperature: +38°C;
- maximum ambient humidity: 60% HR;
- o height-adjustable feet;
- internal dimensions mm. 620x700x1396h.

Supplied:

- o n.3 GN 2/1 grills;
- o n.6 guides.

CE mark

TECHNICAL CARD	
power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,305
net weight (Kg)	108
gross weight (Kg)	123
breadth (mm)	740
depth (mm)	830
height (mm)	2010

