



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TP-KB32-R</b>	HOT countertop DISPLAY CABINET, with 2 TIERS, STAINLESS STEEL STRUCTURE, glass on 4 sides, plexiglass FALLING DOORS on operator side, complete with HUMIDIFIER, temperature from +30° to +90°C, suitable for GN 2/3, V containers .230/1, Kw.0.5, dim.mm.370X370X390h	<b>€ 384,20</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days

#### PROFESSIONAL DESCRIPTION

**HOT countertop display cabinet, with 2 shelves in STAINLESS STEEL, suitable for GASTRO-NORM 2/3 containers:**

- **furnishing object** capable of **enhancing the product on display and the environment** in which it is installed;
- **stainless steel sheet structure** , with scotch brite brushed finish;
- **glass on 4 sides** for displaying baked pastry products, brioches, croissants, muffins, etc.;
- the **useful space** in height **for the shelves is 15 cm** ;
- **drop-down** plexiglass doors **on the operator side** ;
- **2 stainless steel shelves** ;
- **heating obtained** with a **high-efficiency radiant resistance** housed in a special container, controlled by a **thermostat adjustable from +30° to +90°C** and indicator light;
- a stainless steel water drawer allows **the humidification of the products** ;
- base frame is supplied with removable tray, suitable for housing **Gastro-Norm 2/3 containers** ;
- uprights with a rounded square section and, together with the upper frame, give the structure **exceptional sturdiness** ;
- **sides and front** are in 4 mm thick **tempered glass** ;
- the **upper surface** is made of 5 mm thick **tempered glass** , fixed to the structure with 4 sturdy large-head screws;
- the hinges applied with pressure screws allow **the door to open almost completely** (170°);
- on-off light switch, plug-in cable with plug;
- Adjustable feet for perfect leveling.

**ACCESSORIES/OPTIONALS:**

- Upon request, drop doors on 2 sides (self-service use).
- On request intermediate glass shelves.

**CE Made in Italy brand**

#### TECHNICAL CARD

**power supply** | Monofase

<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,5
<b>net weight (Kg)</b>	11
<b>breadth (mm)</b>	370
<b>depth (mm)</b>	370
<b>height (mm)</b>	390