



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
EM-SYSTEM40	BELL VACUUM PACKAGING MACHINE for counter, SYSTEM Line, CHAMBER mm. 410x450x220h, 400 mm WELDING BAR, 20 m / cubic / hour VACUUM PUMP, V.230 / 1, Kw. 0.90, Weight Kg. 60, external dimensions mm.510x560x450h	€ 1.858,71 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days

PROFESSIONAL DESCRIPTION

COUNTER BELL VACUUM PACKAGING MACHINE, SYSTEM Line with DIGITAL CONTROLS :

- **New series** of digital counter top packaging machines;
- Equipped with **brand new electronic card** ;
- **Digital control panel with 3** editable and customizable programs;
- **1 program for marinating meat** ;
- **400 mm sealing bar** with completely renewable wiring;
- Pump self- **cleaning / heating system** for optimal management of the packaging machine, reducing maintenance times and costs;
- **GASTROVAC function** for creating external vacuum in GN containers;
- **EXTRAVAC function** , which offers a **second vacuum phase lasting 5 seconds** (particularly suitable for minced and boned meat);
- Quick stop / welding;
- Carter with 90 ° opening to facilitate access to the inside of the packaging machine;
- **Vacuum chamber 410x450x220h mm** , made of stainless steel molded in a single piece with rounded corners for maximum hygiene and easy cleaning;
- **20 meters / cubic / hour vacuum pump** ;
- **Simple and immediate electronics** , 18-level sealing for any type of bag;
- **Note** : Possibility of **external vacuum with the use of embossed envelopes** , (as shown in the photo).

OPTINAL / ACCESSORIES:



- Possibility of **vacuuming in external containers** or **gastro-norm basins** using a special kit - Code EMATUBOBN.
- Predisposition for **inert gas kit** - Code EMGASINERTE.
- Sealing **bar with piston lifting** - Code EMBSP.
- Sealing **bar with envelope excess cut (scrap)** - Cod. EMTS.
- Bell stop bar - Code EMBF.
- Inclined plane for liquid packaging - Code EMPI.
- Machine support trolley - Code EMCR.

CE mark
Made in Italy

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	5060
motor power capacity (Kw)	0,9
net weight (Kg)	60
breadth (mm)	510
depth (mm)	560
height (mm)	450

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<p>EM-BF</p> 	<p>TECHNOCHEF - Bell holder, Mod.BF Bell stop bar</p>	<p>€ 24,99 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days</p>
<p>EM-BSPVE</p> 	<p>Sealing bar with piston Piston lifting sealing bar</p>	<p>€ 79,61 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days</p>



Inclined plane, Mod.PI
Inclined surface for liquid packaging, suitable for bell-shaped packaging machines

€ 85,74
VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days



Tube with adapter sleeve in gastro containers
Tube with adapter sleeve in gastro containers

€ 102,01
VAT excluded
Shipping to be calculated

Delivery



Gas inert, Mod.GSR
Inert gas kit for chamber vacuum machines

€ 242,57
VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days



Machine Support Trolley, Mod.CR
Support trolley

€ 282,20
VAT excluded
Shipping to be calculated


Delivery from 4 to 9 days




STANDARD FUNCTIONS PER CONFEZIONATRICI A CAMPANA
STANDARD FUNCTION ONLY FOR CHAMBER MACHINES



Pannello digitale
Digital panel



Sistema autopulizia olio
Oil made auto cleaning system



Pannello comandi a totale tenuta
contro umidità
Waterproof control Panel



Carter apribile a 90°
90° openable carter



Barre saldanti estraibili
Removable sealing bars



Vasca inox con angoli stondati
senza saldature
Entirely printed stainless steel
vacuum chamber, with internal
round corners



Connessione per attacco gastrovac
Connection for the gastrovac system



Set tavole di riempimento in
polietilene
Polyethylene filling squares set



OPTIONAL PER CONFEZIONATRICI A CAMPANA
OPTIONALS ONLY FOR CHAMBER MACHINES



Installazione gas inerte
 Arrangement for idle gas



Vasca doppia altezza per confezionamento liquidi (SYSTEM 40)
 Special double height vacuum chamber to pack liquids (SYSTEM 40)



Pompa Busch
 Busch Pump



Saldatura con pistoni senza cavi
 Sealing with cableless pistons



Tensione e frequenza speciale
 Voltage and special frequency



Carricelli supporto macchina
 Chariot on wheels



Taglio Eccedenza
 Exceeding cutting bar



Sistema bloccaggio campana
 Lif Hook



Piano inclinato per liquidi
 Inclined plane for liquids



Modifica parametri vuoto / saldatura / tempo immissione gas
 - Attivazione / Disattivazione GAS INERTE
 used to modify vacuum/sealing/gas injection time parameters
 - connection/disconnection of inert gas

Funzione Gas Inerte
 Attivata (LED ACCESO)
 Inert gas function on
 (LED on)

1. Settaggio % di vuoto
2. Settaggio tempo di saldatura
3. Attivazione funzione saldatura rapida
4. Attivazione funzione VAC STOP: interruzione anticipata del ciclo di vuoto

1. Setting of the vacuum percentage
2. Setting of the sealing time
3. Activation of RAPID SEALING: if you push the button once
4. Activation of VAC STOP FUNCTION (stop in advance the vacuum cycle) if you push the button twice



Accensione / Spegnimento
 confezionatrice
 switch on / switch off of the
 vacuum packaging machine

Funzione di vuoto in
 continuo, per aspirazione
 in contenitori gastro
 nonstop vacuum function done
 with suction in gastro bowls

Definizione della percentuale di
 vuoto raggiunta in camera
 vacuum level reached in the
 chamber

Funzione di pulizia olio pompa del
 vuoto.
 Premendo il tasto per tre secondi
 a campana chiusa
 pushing the button for three
 seconds (only when the bell is
 closed) the cleaning function of
 the vacuum pump begins

Definizione tempo di saldatura
 (espresso in secondi)
 sealing time (in seconds)