



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>AG-LCT-R</b>	Stainless steel vegetable washer/extractor with water recovery tank, capacity 48 litres, speed 350 rpm, V.230/1, Kw.0.66, Weight 115 Kg, dim.mm.850x600x850h	<b>€ 8.658,92</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> Delivery from 8 to 15 days

**PROFESSIONAL DESCRIPTION**

**VEGETABLE WASHER/JUICER in STAINLESS STEEL, with RINSE WATER RECOVERY TANK:**

- specially designed for **washing** and **drying fruit** and **vegetables** , but also for **washing** and **defrosting meat** and **fish** in medium-large professional kitchens and in the food industries;
- thanks to the multiple functions and the high degree of automation, the **processes are carried out quickly and effectively** ;
- **structure** , **stainless steel washing tank** and water recovery tank;
- **removable basket in ultra-light Inoxal®** ;
- single speed motor;
- **tank capacity** : 48 litres;
- **load** : **leafy vegetables 2.5-3 kg** , **heavy vegetables 12-15 kg** , **meat or fish 10-12 kg** ;
- **complete wash-rinse-drying cycle duration 7 min** ;
- **speed** : 350 rpm;
- **purification and recovery of rinse water load for subsequent washing** ;
- IPX protection class 2;
- **safety micro on the lid** ;
- **electric brake for immediate engine stop in centrifugal operation** ;
- **pressure switch for regulating the water level in the wash tank** ;
- **pressure switch for regulating the water level in the recovery tank** ;
- **turbulence washing** controlled by flow adjustment knob;
- ergonomic control panel with function keys and programmable mechanical timer.

**CE mark**  
**Made in Italy**

**TECHNICAL CARD**

**power supply** | Monofase

<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,66
<b>net weight (Kg)</b>	115
<b>breadth (mm)</b>	850
<b>depth (mm)</b>	600
<b>height (mm)</b>	850



**CESTELLO CENTRIFUGO**